

LED Linear Highbay INSTALLATION INSTRUCTION

Please read the user manual carefully and follow it. This will help to prevent damage of the product, prolong its lifespan; And it will be helpful for your normal use and maintenance, to ensure that you life safety. Please keep the manual properly.

WARNING

- Risk of fire. Turn off power before installation.
- Risk of electronic shock. Install only by certified electrician with gloves.
- To be used in indoor dry and damp location only.
- If the luminaire exhibits undesirable operation (buzzing, flickering, not working etc.) ,immediately turn off power, remove luminaire and contact manufacturer.
- Do not make mass installation before testing.



Parameters

SKU	Input Voltage	CCT	Power	Rated Current	Produce Size
A-HBL2FT95/105/115/125W-NV-AUX12-5K	AC120-277V 50-60HZ	5000K	95/105/115/125W	0.5A Max	24.13"*12.08"*2"
A-HBL4FT190/210/230/250W-NV-AUX12-5K	AC120-277V 50-60HZ	5000K	190/210/230/250W	1.2A Max	46.26"*12.08"*2"

INSTALLATION FOR SUSPENDED MOUNTING

1. Always turn off power before installation, install the hanging cable . Please See Step ①② .
2. Adjust the height of hanging cables and put the pipe or metal tube through the slide door, connect the wiring according to the local code. Please See Step ③.
3. Put the pipe or tube into the driver junction box, screw the slide door. Please See Step④.
4. Turn on the power, the fixture will illuminate. Please See Step ⑤.

