

Highbay Vapor Tight Strip INSTALLATION INSTRUCTION

Please read the user manual carefully and follow it. This will help to prevent damage of the product, prolong its lifespan; And it will be helpful for your normal use and maintenance, to ensure that you life safety. Please keep the manual properly.

WARNING

- Risk of fire. Turn off power before installation.
- Risk of electronic shock. Install only by certified electrician with gloves.
- To be used in indoor dry and damp location only.
- If the luminaire exhibits undesirable operation (buzzing, flickering, not working etc.) ,immediately turn off power, remove luminaire and contact manufacturer.
- Do not make mass installation before testing.



Parameters

SKU	Input Voltage	CCT	Power	Rated Current	Produce Size
A-VT2FT12/18/25/30W-NV-AUX12-345K	AC120-277V 50-60HZ	3500/4000/5000K	12/18/25/30W	0.5A Max	23.62"*4.35"*3.5"
A-VT4FT25/35/40/50W-NV-AUX12-345K	AC120-277V 50-60HZ	3500/4000/5000K	25/35/40/50W	0.6A Max	47.24"*4.35"*3.5"
A-VT8FT45/60/70/80W-NV-AUX12-345K	AC120-277V 50-60HZ	3500/4000/5000K	45/60/70/80W	0.8A Max	94.02"*4.33"*3.5"

INSTALLATION FOR SUSPENDED MOUNTING

1. Disconnect or turn off power before installation. See step ①.
2. Install the snap bracket on the ceiling. See step ②.
3. Make the electrical connection to the fixture in accordance with local electrical code. Make all necessary wiring connections, observing proper voltage and polarity. See step ③.
4. Connect the PCB board to the body. See step ④.
5. Secure the lens with buckles. See step ⑤.
6. Attach the entire fixture to the snap bracket. See step ⑥.
7. Connect or turn on the power, the light will be on, see step ⑦.

